

Appl. No. 09/314,615

Reply to Office Action of January 16, 2003

**Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (currently amended): An apparatus for directing audio signals between audio transducers and a system, comprising:

a plurality of ports for communicating audio signals with a plurality of audio transducers, at least one of the audio transducers having off hook capability;

a transducer switch, coupled to the plurality of ports, that receives a configuration for the plurality of audio transducers and that, in response to detecting an off hook condition of at least one of the audio transducers having off hook capability, switches audio signals from one of the audio transducers to the off hook audio transducer for which the off hook condition was detected; and

wherein said transducer switch includes:

a controller that receives said configuration; and

a switch, coupled to the plurality of ports and to said controller; and

wherein said switch switches responsive to receiving a signal from said controller to indicate detection of said off hook condition.

Claim 2 (canceled)

Claim 3 (currently amended): The apparatus of claim 1, wherein the switch receives a signal from the controller when the off hook audio transducer goes on hook and switches audio signals back from the on hook audio transducer to the one of the audio transducers:

Claim 4 (currently amended): The apparatus of claim 1, wherein the switch includes a first switch for selecting one of the audio transducers that does not have

Appl. No. 09/314,615

Reply to Office Action of January 16, 2003

off hook capability and a second switch for selecting between the audio transducer selected by the first switch and an audio transducer that has off hook capability.

Claim 5 (currently amended): The apparatus of claim 1 2, wherein the controller receives the configuration for the plurality of audio transducers from a computer system.

Claim 6 (original): The apparatus of claim 1, wherein the off hook audio transducer is a normal telephone or conference telephone.

Claim 7 (original): The apparatus of claim 1, wherein the plurality of audio transducers are near field microphones, far field microphones, headsets, handsets, auxiliary inputs/outputs, speakers, amplifiers, normal telephone, or conference telephone.

Claim 8 (original): The apparatus of claim 1, further comprising:  
audio circuitry that communicates audio signals between the transducer switch and the system, said system comprising a computer system.

Claim 9 (original): The apparatus of claim 8, wherein said at least one of the audio transducers is a telephony device.

Claim 10 (original): The apparatus of claim 8, wherein said apparatus comprises a sound card internal to said computer system.

Claim 11 (original): The apparatus of claim 8, wherein the sound card is external to the computer system.

Claim 12 (original): The apparatus of claim 1, wherein the apparatus is for use with a computer telephony client.

Claim 13 (original): The apparatus of claim 1, wherein apparatus is for use with a voice recognition system, messaging system, or audio server.

Appl. No. 09/314,615

Reply to Office Action of January 16, 2003

Claim 14 (previously presented): A method of managing audio transducers, comprising:

receiving a configuration for a plurality of audio transducers, said configuration specifying that audio signals are to be sent to a first audio transducer and received from a second audio transducer;

detecting that a third audio transducer has been turned on;

changing the configuration such that audio signals are sent to the third audio transducer instead of the first audio transducer; and

changing the configuration such that audio signals are received from the third audio transducer instead of the second audio transducer.

Claim 15 (canceled)

Claim 16 (previously presented): The method of claim 14, further comprising:

detecting that the third audio transducer has been turned off; and

restoring the configuration such that audio signals are sent to the first audio transducer instead of the third audio transducer.

Claim 17 (original): The method of claim 14, further comprising setting the configuration in an audio device between the plurality of audio transducers and a computer system, wherein said configuration is received from the computer system.

Claim 18 (original): The method of claim 17, wherein the configuration is input by a user utilizing a graphical user interface (GUI).

Claim 19 (original): The method of claim 18, further comprising:  
allowing a user to select one of an input or output audio transducer; and  
automatically selecting a default corresponding input or output audio transducer according to the user's selection.

Appl. No. 09/314,615  
Reply to Office Action of January 16, 2003

Claim 20 (original): The method of claim 14, wherein the third audio transducer is a telephony device and is turned on by going off hook.

Claim 21 (original): The method of claim 14, further comprising setting the configuration in an audio device coupled to the plurality of audio transducers, said audio device being a sound card.

---